

PRE-INSTALLATION NOTES, CLEANING AND MAINTENANCE

PRE-INSTALLATION NOTES

- It is extremely important that you correctly read and understand the information given before starting with the installation as an incorrect use or maintenance of the installation may result in the cancelation of the manufacturer's warranty.
- Carefully inspect ALL material prior to installation, in order to verify that it has no defects. Materials installed with visible defects are not covered by this warranty.
- If you are not satisfied with the material prior to installing, please contact your dealer. DO NOT INSTALL.
- We recommend that, as a final inspector, you examine the color, finish, style, and quality BEFORE installing. Verify that the material is right. We will not be liable for any expenses incurred once the pieces with visible defects are installed.
- It is the installer's and owner's responsibility to ensure that working conditions and the work area are suitable, before installing the material.

CLEANING AND MAINTENANCE

Cleaning

For the best results, wipe with water and dry. **DO NOT USE PRODUCTS THAT CONTAIN ACIDS.**

Tips

- Avoid using dyes and permanent marker.
- Do not use abrasive utensils or tools.
- Does not require sealing; however, it is a good idea to seal grout or any joints.
- Grout needs to be cleaned on a periodic basis to remove any surface buildup. Grout cleaning can be done with a daily concentrated household or commercial cleaner depending on the application.
- Routine cleaners should never contain harsh chemicals as these can damage tile. Acids can damage grout and the glazed surface of the tile. Ammonia can discolor grout.