# **BRICK HAUS**







## **AVAILABLE IN:**

#### 9mm Wall Dimensional

Rectified Edge

6"x15.6" Ocean Natural Finish 6"x15.6" Breccia Natural Finish 6"x16" Old Wall Natural Finish

- All sizes are NOMINAL





Ocean White Mix





Breccia Grigio

**Breccia Antracite** 



Old Wall Beige



Old Wall Grey

Colors shown may vary from actual product. Final selection should be made from actual product samples.



Breccia Rock Mix



Old Wall Multicolor





# GENROSE

Features	Test Method	Value
Water Absorption	ASTM C 373	≤ 0.6%
Breaking Strength	ASTM C 648	Average ≥ 250 lbf (1.11 kN) Individual ≥ 225lbf (1.00 kN)
Thermal Shock Resistance	ASTM C 428	Resistant
Bond Strength	ASTM C 482	> 1 MPa
Mohs Hardness Scale	EN 101	≥ 5
Chemical Resistance	ASTM C 650	Resistant
Stain Resistance	ASTM C 1378	Resistant
Recycled Content	-	Min. 40%

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

#### Product Info:

- Glazed Porcelain Tile
- Natural Finish •
- 9mm Thickness •
- Rectified Edge •
- V4 EXTREME Variation
- Frost Resistance = Yes

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.

### **BRICK HAUS**

Glazed Porcelain Tile



www.genrose.com



www.genrose.com