DEMURE







3"x24" Field Tile in Grigio



13"x14" Freccia Mosaic in Grigio

AVAILABLE IN:

10mm Field Tiles

Rectified Edge

3"x12" Natural Finish 3"x24" Natural Finish 12"x24" Natural Finish

Trim Piece

3"x24" Bullnose Natural Finish



Mosaics + Decos

2"x2"	Mosaic Natural Finish*
3"x3"	Mosaic Natural Finish
12"x12"	Mosaic Mix Natural Finish
12"x12"	Diamond Deco Natural Finish
13"x14"	Freccia Mosaic Natural Finish

^{*}Only available in Grigio and Nero

MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
Any 24" field tile can be cut down to			2" 4"		1 ³ / ₈ "x3" 2"x4"
	a smaller size in any length and width combination with a 1" minimum.	BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" ⁵ / ₈ "x4"
○ Diamond	4"			* > > >	78 X4
		OCTAGONS		HEXAGONS	
Hexagon	6"	888888	- "		
Chevron	2"x12" 6"x24"		2" w/ 0.6" Squares		1 ¹ / ₈ " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ ⁵ / ₈ " Dot		1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3"		1"x2" 1"x4"

^{*}Other sizes available upon request

⁻ All sizes are NOMINAL





Taupe Bianco





Grigio Nero

2"X2" MOSAIC



Grigio



3"X3" MOSAIC



Bianco



Taupe



Grigio



Nero

2D MOSAIC MIX





12"X12" DIAMOND DECO



Taupe



Grigio



Nero

14"X13" FRECCIA



Taupe



Grigio



Nero



Features	Test Method	Value	
Length and Width		± 0.6%	
Thickness	ISO 10545-2	± 5%	
Wedging	150 10343-2	± 0.6%	
Warpage		± 0.5%	
Water Absorption	ISO 10545-3	≤ 0.5%	
Bending Strength	ISO 10545-4	≥ 35 N/mm²	
Deep Abrasion Resistance	ISO 10545-6	149	
Coefficient of Linear Thermal Expansion	ISO 10545-8	9X10-5XC-1	
Rersistance to Thermal Shock	ISO 10545-9	Resistant	
Crazing Resistance	ISO 10545-11	Resistant	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	GAV/GLAV	
Stain Resistance	ISO 10545-14	Min. Class 5	
DCOF (WET)	BOT 3000	≥ 0.53	
Slip Resistance	DIN 51130	R10	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Natural Finish
- 10mm Thickness
- Rectified Edge
- V3 Moderate Variation



www.genrose.com



www.genrose.com