

10"x40" Field Tile in Suisi

AVAILABLE IN:

9mm Field Tiles

Rectified Edge


10"x40" Natural | Anti-Slip Finish 6"x40" Natural | Anti-Slip Finish

Deco and Mosaic

6"x6" Mixed Deco Natural Finish
1"x1" Mosaic Natural Finish

Trim Pieces

3"x40" Bullnose Natural Finish 20"x1.5" Torello Natural Finish 6"x12"x1.5" Elemento L Anti-Slip Finish











Siusi Gardena





Fiemme Badia



2"X2" MOSAIC









Siusi

Gardena

Fiemme

Badia

6"X6" MIXED DECO



















Features	Test Method	Value	
		7cm ≤ N < 15 cm	N ≥ 15 cm
Sides	ISO 10545-2	± 0.9 mm	± 0.6% (± 2.0 mm)
Thickness	ISO 10545-2	± 0.5 mm	± 5.0% (± 0.5 mm)
Straightness of Sides	ISO 10545-2	± 0.75 mm	± 0.5 % (± 1.5 mm)
Rectangularity	ISO 10545-2	± 0.75 mm	± 0.5% (± 2.0 mm)
Surface Flatness	ISO 10545-2	± 0.75 mm	± 0.5% (± 2.0 mm)
Water Absorption	ISO 10545-3	≤ 0.1%	
Breaking Strength	ISO 10545-4	≥ 1300 N	
Bending Strength	ISO 10545-4	≥ 35 N/mm²	
Impact Resistance	ISO 10545-5	> 0.80	
Coefficient of Linear Thermal Expansion	ISO 10545-8	6.7x10 ⁻⁶ /C°	
Resistance to Thermal Shocks	ISO 10545-9	Resistant	
Moisture Expansion	ISO 10545-10	MAX 0.1 mm / m	
Frost Resistance	ISO 10545-12	Resistant	
Chemical Resistance	ISO 10545-13	B Min	
Resistance to Stains	ISO 10545-14	Class 3 Min	
Lead and Cadmium	ISO 10545-15	< Than Instrument Limit	
DCOF (WET)	ANSI A 137.1	> 0.42	

This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.

According to ANSI and MIA standards. depending on the type and size of tile. it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Natural | Anti-Slip Finishes
- 9mm ThicknessRectified Edge
- PEI Rating = 4
- V4 Substantial Variation
- Frost Resistance = Yes



www.genrose.com



www.genrose.com