

**RENOWN**

 **GENROSE**



# AVAILABLE IN:

## 9mm Field Tiles

Rectified Edge

- 3"x12" Polished Finish
- 6"x12" Matte Finish
- 12"x24" Matte | Polished Finish
- 24"x24" Matte | Polished Finish
- 24"x48" Matte | Polished Finish

## Mosaics

- 2"x2" Mosaic
- 5/8"x4" Herringbone Mosaic
- 3" Hexagon Mosaic
- Matte Finish
- Polished Finish
- Matte Finish

- All sizes are NOMINAL




White



2"x2" Mosaic



3" Hexagon Mosaic



5/8"x4" Herringbone Mosaic

Colors shown may vary from actual product. Final selection should be made from actual product samples.



# MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer. We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 3/8"x3" 2"x4"
<b>FIELD SHAPES*</b> Half Hexagon 6.7" Base Diamond 4" Hexagon 6" Chevron 2"x12" 6"x24"		BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 3/8"x3" 2"x4"		2"
		CHEVRONS		HERRINGBONE	
			2"x12"		1"x2" 2"x4" 5/8"x4"
		OCTAGONS		HEXAGONS	
			2" w/ 0.6" Squares		1 1/8" 2"
<b>TRAPEZOID W/ DOT</b>		<b>SQUARES</b>		<b>RECTANGLES</b>	
	4"x2 1/2" w/ 5/8" Dot		1"x1" 2"x2" 1 3/8"x1 3/8" 3"x3"		1"x2" 1"x4"

\*Other sizes available upon request

Features	Test Method	Value	
		Matte	Polished
<b>DCOF (Wet)</b>	ANSI A 137.1	≥ 0.42	n/a
<b>Breaking Strength</b>	ANSI C648	≥ 425 lbf	
<b>Scratch Hardness (MOHS)</b>	-	7	4-5
<b>Water Absorption</b>	ASTM C373	< 0.5%	
<b>Chemical Resistance</b>	ASTM C650	Class B	Class E
<b>Abrasion Resistance</b>	ASTM C1027	Class 3	
<b>Thermal Shock Resistance</b>	ASTM C484	Resistant	
<b>Frost Resistance</b>	ASTM C1026	Resistant	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Glazed Porcelain Tile
- Matte | Polished Finishes
- 9mm Thickness
- Rectified Edge
- PEI Rating = 3
- V3- Moderate Variation
- Frost Resistance = Yes





[www.genrose.com](http://www.genrose.com)