

Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.6%
Thickness		± 5%
Wedging		± 0.6%
Warpage		± 0.5%
Water Absorption	ISO 10545-3	≤ 0.5%
Bending Strength	ISO 10545-4	≥ 35 N/mm ²
Deep Abrasion Resistance	ISO 10545-6	149
Coefficient of Linear Thermal Expansion	ISO 10545-8	9X10-5XC-1
Resistance to Thermal Shock	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	GAV/GLAV
Stain Resistance	ISO 10545-14	Min. Class 5
DCOF (WET)	BOT 3000	≥ 0.53
Slip Resistance	DIN 51130	R10

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Natural Finish
- 10mm Thickness
- Rectified Edge
- V3 - Moderate Variation

