

Features	Test Method	Value
Water Absorption	ASTM C373	≤ 0.5%
Breaking Strength	ASTM C648	≥450 lb _f avg.
Linear Thermal Expansion	ASTM C372	Conforms
Thermal Shock Resistance	ASTM C484	No sample shows visible signs
Chemical Resistance	ASTM 650	Conforms
Stain Resistance	ASTM C1378	Conforms
Freeze/Thaw Resistance	ASTM C1026	Resistant
Bond Strength	ASTM C482	≥ 50 PSI (0.34 MPa)
Thickness	ASTM C499	max ± 0.030 inch
Surface Hardness	Mohs Scale	7 Mohs
Warpage Edge	C485	Conforms
DCOF (Wet)	ANSI A326.3	Pass (Matte Finish Only)
Recycled Material	-	≤40%
  		<p>This product will contribute to USGBC registered LEED points. It will also contribute to the ANSI approved NAHB Green Building Points.</p>

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Matte | Polished Finish
- 9mm Thickness
- Rectified Edge
- Frost Resistance = Yes
- V3 - Moderate Variation
- Check Decor 24 for Stock



www.genrose.com