

Features	Test Method	Value
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	≥ 425 lbs
Abrasion Resistance	ISO 10545-7	Class 3
Thermal Shock Resistance	-	Resistant
Chemical Resistance	ISO 10545-13	Class D
Frost Resistance	ISO 10545-12	Resistant
ANSI Classification	-	IW+
DCOF (WET)	ANSI B101.3	≈ 0.63
Recycled Material	-	12-16%
<p>This product is GREEN-SQUARED® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC</p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



Product Info:

- Glazed Porcelain Tile
- Semi Polished Finish
- 9mm Thickness
- Rectified Edge
- PEI Rating = 3
- V3 - Moderate Variation
- Frost Resistance = Yes



V3 - Moderate variation is inherent in this tile.
All material must be inspected prior to installation.
Absolutely no claims will be accepted after installation.



www.genrose.com