# **ALLURE**









1"x3" Herringbone Mosaic | 0.75"x13" Pencil in Azzuro 3"x12.5" Wall Tile in Glossy White

### **AVAILABLE IN:**

### **8mm Wall Tiles**

Pressed Edge

3"x12.5" Glossy Finish

#### Trim Pieces

0.75"x13" Pencil Glossy Finish 0.5"x12.5" Quartino Glossy Finish

#### Mosaics

1"x3" Brick Mosaic Glossy Finish

1"x3" Herringbone Mosaic Glossy Finish









**Glossy White** 



Bianco Sporco



Salvia




Smeraldo




Azzuro





Fumo Di Londra



Grigio Scuro

### 1"X3" BRICK MOSAIC



## 1"X3" HERRINGBONE MOSAIC







| Features                            | Test Method  | Value                                 |                          |
|-------------------------------------|--------------|---------------------------------------|--------------------------|
| Percentage of Tiles without Defects | ISO 10545-2  | ≥95%                                  |                          |
| Work Size                           | ISO 10545-2  | ± 0.5%/±2.0mm                         |                          |
| Straightness of Sides               | ISO 10545-2  | ± 0.3%/±1.5mm                         |                          |
| Rectangularity                      | ISO 10545-2  | ± 0.5%/±2.0mm                         |                          |
| Edge Curvature                      | ISO 10545-2  | -0.3/+0.5%/-1.5/+2.0mm                |                          |
| Centre Curvature                    | ISO 10545-2  | -0.3/+0.5%/-1.5/+2.0mm                |                          |
| Warpage                             | ISO 10545-2  | ± 0.5%/±2.0mm                         |                          |
| Thickness                           | ISO 10545-2  | ± 10%/±1.5mm                          |                          |
| Water Absorption                    | ISO 10545-3  | E>10% min 9%                          |                          |
| Modulus of Rupture                  | ISO 10545-4  | e≥7.5mm<br>≥600N                      | e<7.5mm<br>≥200N         |
| Breaking Strength                   | ISO 10545-4  | Media ≥12 N/mm²                       | Media ≥15 N/mm²          |
| Linear Thermal Expansion            | ISO 10545-8  | 5.9x10 <sup>-5</sup> °K <sup>-1</sup> |                          |
| Resistance to Thermal Shock         | ISO 10545-9  | Resistant                             |                          |
| Crazing Resistance                  | ISO 10545-11 | Resistant                             |                          |
| Chemical Resistance                 | ISO 10545-13 | Household<br>GA                       | Low Concentration<br>GLA |
| Stain Resistance                    | ISO 10545-14 | 5                                     |                          |

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

#### **Product Info:**

- Ceramic Tile
- Glossy Finish
- 8mm Thickness
- Pressed Edge
- V2 Slight Shading Variation
- Frost Resistance = No



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com