ARCTIC







AVAILABLE STOCKED ITEMS:

10mm Wall Tiles						
SIZE	FIN	ISH	COLORS			
12"x24"	Gloss		White			
	Satin		Alabaster			
8mm Wall T	ïles					
SIZE	FINISH		COLORS			
10"×18"	Gloss		White			
	Satin		Alabaster			
Trim Pieces						
SIZE	ТҮРЕ	FINISH	COLORS			
4.5"X12"	Cove Base	Gloss	White			
.75"X4.5"	Cove Base Corner	Gloss	White			
4.11 4.0.11	Torello Pencil*	Gloss	White			
1"x12"		Satin	Alabaster			
.5″x12″	Finishing Strip	Gloss	White			
		Satin	Alabaster			
1"x12"	Flat Liner*	Gloss	White			
4"X12"	Bullnose on 12" Side	Gloss	White			
4"X12"	Bullnose on 4" Side	Gloss	White			

All Sizes are Nominal. *Glazed on long side.





White

Alabaster



Features	Test Method	Value	
Length / Width		± 0.25%	
Thickness		± 2.5%	
Straightness of Side	EN ISO 10545 - 2	± 0.15%	
Rectangularity		± 0.4%	
Surface Flatness		± 0.2%	
Water Absorption	EN ISO 10545 - 3	15% to 17%	
Weight / M ²	-	8mm Thick 14.85 kg	10mm Thick 17.78 kg
Modulus of Rupture	EN ISO 10545 - 4	$\geq 25 \text{ N} / \text{mm}^2$	
Thermal Shock	EN ISO 10545 - 9	Pass	
Frost Resistance	EN ISO 10545 - 12	Not Suitable	
Chemical Resistance	EN ISO 10545 - 13	Class A - B	
Stain Resistance	EN ISO 10545 - 14	Class 3	
Fire Rating	-	Class A1 Non Combustible	
Recycled Content	-	Up to 20%	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



Product Info:

- Ceramic Tile
- 8mm | 10mm Thicknesses
- Gloss | Satin Finishes
- V1 Uniform Appearance
- Frost Resistance = No

V1





www.genrose.com



www.genrose.com