

ARKITONE

 GENROSE





24"x24" Field Tile in A



24"x48" Field Tile in N

# AVAILABLE IN:

## 10.5mm Field Tile


- 48" x 48" *Matte Finish | Honed Finish*
- 24" x 48" *Matte Finish | Honed Finish*
- 24" x 24" *Matte Finish | Honed Finish | Bush Hammered Finish*
- 12" x 24" *Matte Finish | Honed Finish | Bush Hammered Finish*

## Special Pieces

- 3.7" x 24" Baseboard
- 24" x 48" Kit Step
- 12.8" x 48" Step

## Mosaic

- 1" x 1" *Matte Finish*
- 12" x 24" Sheet *Staggered Mosaic Matte Finish*



- All sizes are NOMINAL

# MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.  
We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 3/8" x 3" 2" x 4"
		BRICKS		DIAMONDS	
			1" x 2" 1" x 3" 1 3/8" x 3" 2" x 4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
	Half Hexagon 6.7" Base		2" x 12"		1" x 2" 2" x 4" 5/8" x 4"
	Diamond 4"	OCTAGONS		HEXAGONS	
	Hexagon 6"		2" w/ 0.6" Squares		1 1/8" 2"
	Chevron 2" x 12" 6" x 24"	SQUARES		RECTANGLES	
	TRAPEZOID W/ DOT 4" x 2 1/2" w/ 5/8" Dot		1" x 1" 1 3/8" x 1 3/8" 2" x 2" 3" x 3"		1" x 2" 1" x 4"

\*Other sizes available upon request



W



G



A



DG




B



N

Colors shown may vary from actual product. Final selection should be made from actual product samples.

# 1"X1" MOSAIC




W




A




B



G



DG



N

# STAGGERED MOSAIC



W



A



B



G



DG



N

Features	Test Method	Fixed Value		
Dimensions And Appearance	ISO 10545-2	Compliant		
Water Absorption	ISO 10545-3	≤ 0.1%		
Flexural Resistance	ISO 10545-4	> 45 N/mm <sup>2</sup>		
Modulus Of Rupture ( Thickness )	ISO 10545-4	8.5mm	2500N	
		12mm	5000N	
		14mm	6500N	
		20mm	11000N	
Resistance to Deep Abrasion	ISO 10545-6	<140 mm <sup>3</sup>		
Resistance to Surface Abrasion	ISO 10545-7	As Indicated In The Catalog		
Linear Expansion Thermic Coefficient	ISO 10545-8	≤ 7X10 <sup>-6</sup> C <sup>-1</sup>		
Resistance to Sudden Temperature Changes	ISO 10545-9	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Resistance of Chemical Attack	ISO 10545-13	High Concentration	Low Concentration	Domestic Chemicals
		Available On Request	GLA, GLB to GLC ULA, ULB to ULC	min. UB / GB
Stain Resistance	ISO 10545-14	Min. 3		
Dynamic Coefficient of Friction (DCOF)	ANSI A137.1	> 0.42 Wet		
Colour Stability to Light	DIN 51094	Compliant		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Through Body Porcelain Tile
- Matte | Honed | Bush-Hammered Finishes
- 10.5mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes





[www.genrose.com](http://www.genrose.com)