## **ARRAY**





## **AVAILABLE IN:**

## 8.5mm Wall Tile

Pressed Edge

3"x12" Glossy Finish

- All sizes are NOMINAL







Milk Cloud Tan

Colors shown may vary from actual product. Final selection should be made from actual product samples.









Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.6% ± 2 mm
Thickness		± 5% ± 0.5 mm
Warpage of Edges		± 0.5% ± 1.5 mm
Wedging		± 0.5% ± 2 mm
Flatness		± 0.5% ± 2 mm
Water Absorption	ISO 10545-3	≤ 0.5%
Bending Strength	ISO 10545-4	R ≥ 35 N/mm²
Coefficient of Linear Thermal Expansion	ISO 10545-8	7x10 <sup>-6</sup> C <sup>-1</sup>
Thermal Shock Resistance	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	Resistant
Stain Resistance	ISO 10545-14	≥ Class 3
Color Resistance to Light	DIN 51094	No Alteration
Slip Resistance	DIN 51130	9 ≤ R ≤ 13
	DIN 51097	А, В, С

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

## **Product Info:**

- Ceramic Tile
- Glossy Finish
- 8.5mm Thickness
- Pressed Edge
- V2 Slight Shading Variation
- Frost Resistance = No





www.genrose.com



www.genrose.com