







8"x48" Field Tile in Beige Cracked



12"x48" Field Tile in Black





12"x48" Field Tile in Brown  
6"x48" Field Tile in Brown | Brown Cracked



6"x48" Field Tile in Black Cracked  
12"x48" Field Tile in Beige





8"x48" Field Tile in Beige Cracked



24"x24" Field Tile in Black | Black Cracked



# AVAILABLE IN:

## 9mm Field Tiles


Rectified Edge

- 12"x48" Natural | Anti-Slip Finish
- 8"x48" Natural | Anti-Slip Finish
- 6"x48" Natural | Anti-Slip Finish
- 24"x24" Natural | Anti-Slip Finish

## Trim Pieces

- 14"x48" Step\*
- 14"x48" Corner Step\*
- 3"x24" Bullnose\*

- All sizes are NOMINAL  
 \* Not available in Cracked



Beige



Beige Cracked

# MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.  
 We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 3/8" x 3" 2" x 4"
		BRICKS		DIAMONDS	
			1" x 2" 1" x 3" 1 3/8" x 3" 2" x 4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
	6.7" Base		2" x 12"		1" x 2" 2" x 4" 5/8" x 4"
	4"	OCTAGONS		HEXAGONS	
	6"		2" w/ 0.6" Squares		1 1/8" 2"
	2" x 12" 6" x 24"	SQUARES		RECTANGLES	
TRAPEZOID W/ DOT			1" x 1"    2" x 2" 1 3/8" x 1 3/8"    3" x 3"		1" x 2" 1" x 4"
	4" x 2 1/2" w/ 5/8" Dot				



Brown



Brown Cracked



Black



Black Cracked

\*Other sizes available upon request

Colors shown may vary from actual product. Final selection should be made from actual product samples.





Features	Test Method	Value
Length and Width	ISO 10545-2	± 0.2%
Thickness	ISO 10545-2	± 5%
Warpage of Edges	ISO 10545-2	± 0.2%
Wedging	ISO 10545-2	± 0.2%
Warpage	ISO 10545-2	± 0.2%
Water Absorption	ISO 10545-3	≤0.1%
Modulus of Rupture	ISO 10545-4	50 N/mm <sup>2</sup>
Breaking Stress	ISO 10545-4	>1700 N
Coefficient of Linear Thermal Expansion	ISO 10545-8	6.5x10 <sup>-6</sup> °C <sup>-1</sup>
Resistance to Thermal Shock	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	GB Min.
Stain Resistance	ISO 10545-14	Class 3 Min.
Slip Resistance	DIN51130	Natural - R9 Anti-Slip - R11
Recycled Material	-	>40%

This product contribute to USGBC registered LEED projects.  
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Natural | Anti-Slip Finishes
- 9mm Thickness
- Rectified Edge
- PEI Rating = 4
- V4 - Substantial Variation
- Frost Resistance = Yes





[www.genrose.com](http://www.genrose.com)