# **CEMENTO**







12"x24" | 18"x36" | 24"x24" Field Tile in G



2"x2" Mosaic in N 12"x24" Field Tile in N 12"x24" Field Tile W

## **AVAILABLE IN:**

### 9mm Field Tile

Pressed Edge

18"x18" Natural Finish

### 10mm Field Tiles

Rectified Edge

12"x24" Natural | Grip Finish 24"x24" Natural | Grip Finish 18"x36" Natural Finish


- All sizes are NOMINAL

### Mosaics + Special Shapes

24"x24" Hexagon Natural Finish
2"x2" Mosaic Natural Finish
Hexagon Mosaic Natural Finish

#### Trim Pieces

4"x18"	Bullnose Natural Finish		
4"x24"	Bullnose Natural Finish		
6"x12"	Stair Bullnose Natural Finish		
13"x36"	Stair Bullnose Natural Finish		



## MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
Any 24" field tile can be cut down to			2" 4"		1 <sup>3</sup> / <sub>8</sub> "x3" 2"x4"
	a smaller size in any length and width combination with a 1" minimum.	BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 <sup>3</sup> / <sub>8</sub> "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4"
Diamond	4"			* > > >	<sup>5</sup> / <sub>8</sub> "×4"
		OCTAGONS		HEXAGONS	
Hexagon  Chevron	6" 2"x12" 6"x24"		2" w/ 0.6" Squares		1 <sup>1</sup> / <sub>8</sub> " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 <sup>1</sup> / <sub>2</sub> " w/ <sup>5</sup> / <sub>8</sub> " Dot		1"x1" 2"x2" 1 <sup>3</sup> / <sub>8</sub> "x1 <sup>3</sup> / <sub>8</sub> " 3"x3"		1"x2" 1"x4"

<sup>\*</sup>Other sizes available upon request









G



## 2"X2" MOSAIC



## **HEXAGON MOSAIC**



## 24"X24" HEXAGON







Features	Test Method	Value	
Slip Resistance	DIN 51130 (R)	Natural - R10 Grip - R11	
Sup Resistance	DIN 51097 (A+B+C)	А	
	BCR REP. CEC 6/81	G.A. > 0.4 G.B. > 0.4	
	DM 14/6/89 N. 236	C.A. > 0.4 G.B. > 0.4	
	Pendulum Test BS	Natural - > 25 Grip - > 36	
DCOF	BOT 3000	> 0.42	



This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

#### **Product Info:**

- Through Body Porcelain Tile
- Natural | Grip Finish
- 9mm | 10mm Thickness
- Pressed | Rectified Edge
- V2 Slight Shading Variation
- Frost Resistance = Yes



www.genrose.com



www.genrose.com