# **CITADEL**









Hexagon Mosaic in Honesty 12"x24" | 3.75"x12"Field Tile in Honesty

### **AVAILABLE IN:**

#### 10mm Porcelain Field Tile

### 24"x24" Matte | Polished Finish 12"x24" Matte | Polished Finish 8"x24" Matte | Polished Finish

#### 10mm Ceramic Trim Pieces

2.4"x12" Listello Glossy Finish 2"x12" Chair Rail Glossy Finish 2"x1" Chair Rail Stops Glossy Finish

#### 10mm Porcelain Mosaics

2"x2" Mosaic Matte Finish

3"x3" Hexagon Mosaic Matte | Polished Finish

Matte | Polished Finish

#### 10mm Porcelain Trim Pieces

3"x12" Bullnose Matte | Polished Finish



3.75"x12"



## MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
Any 24" field tile can be cut down to a smaller size in any length and width		2" 4"		1 <sup>3</sup> / <sub>8</sub> "x3" 2"x4"	
	length and width combination with a 1" minimum.	BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 <sup>3</sup> / <sub>8</sub> "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" <sup>5</sup> / <sub>8</sub> "x4"
Diamond	4"	OCTA	GONS	HEAV	GONS
( Hexagon	6"	0014	2"	IILAA	
Chevron	2"x12" 6"x24"		w/ 0.6" Squares		1 <sup>1</sup> / <sub>8</sub> " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 <sup>1</sup> / <sub>2</sub> " w/ <sup>5</sup> / <sub>8</sub> " Dot		1"x1" 2"x2" 1 <sup>3</sup> / <sub>8</sub> "x1 <sup>3</sup> / <sub>8</sub> " 3"x3"		1"x2" 1"x4"







**Honesty** Beauty






Grace Charm

## 2"X2" MOSAIC









Honesty

**Beauty** 

Grace

Charm

### **HEXAGON MOSAIC**









Honesty

2.4"X12" LISTELLO









Honesty

Beauty

Grace

Charm

## 2"X12" CHAIR RAIL AND 2"X1" CHAIR RAIL STOP















Features	Value		
	Matte	Polished	
Water Absorption	≤ 0.5%	≤ 0.5%	
DCOF AcuTest	Pass	Fail	
Surface Hardness	7 mohs	6 mohs	
Breaking Strength	≥396 lbf	≥600 lbf	
Recycled Material	≥40%	≥40%	



This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

#### **Product Info:**

- Glazed Porcelain and Ceramic Tile
- Matte | Polished | Glossy Finish
- 10mm Thickness
- Rectified Edge
  - PEI Rating = 3 Beauty | Charm | Grace
    - 4 Honesty
  - Frost Resistance = Yes
- V3 -Moderate Variation



www.genrose.com



www.genrose.com