

DISTANCE



GENROSE





8"x48" Field Tile in Wheat



8"x48" Field Tile in Malt

AVAILABLE IN:

8.5mm Field Tile			
SIZE	FINISH	COLORS	
8"x24"	Matte	Spirit Barley Proof Wheat Malt	
Mosaic			
SHEET SIZE	TYPE	FINISH	COLORS
10"x13"	Twist Mosaic	Matte	Barley Warm Mix Cool Mix



Spirit



Barley



Proof



Wheat



Malt

MADE TO ORDER FIELD TILES AND MOSAICS:

Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile can be cut down to a smaller size in any length and width combination with a 1" minimum.		2" 4"		1 3/8" x 3" 2" x 4"
		BRICKS		DIAMONDS	
			1" x 2" 1" x 3" 1 3/8" x 3" 2" x 4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
	Half Hexagon 6.7" Base		2" x 12"		1" x 2" 2" x 4" 5/8" x 4"
	Diamond 4"	OCTAGONS		HEXAGONS	
	Hexagon 6"		2" w/ 0.6" Squares		1 1/8" 2"
	Chevron 2" x 12" 6" x 24"	SQUARES		RECTANGLES	
	TRAPEZOID W/ DOT 4" x 2 1/2" w/ 5/8" Dot		1" x 1" 1 3/8" x 1 3/8" 2" x 2" 3" x 3"		1" x 2" 1" x 4"

*Other sizes available upon request

All Sizes are Nominal.

Colors shown may vary from actual product. Final selection should be made from actual product samples.

TWIST MOSAIC



Cool Mix



Barley



Warm Mix



8"x48" Field Tile in Barley



DISTANCE
Glazed Porcelain Tile

Features	Test Method	Value
Thickness	C499	max ± 0.030 inch
Water Absorption	C373	≤ 0.5%
Breaking Strength	C648	≥ 350 lbf. avg.
Linear Thermal Expansion	C372	Not Required
Thermal Shock Resistance	C484	No sample must show visible signs
Chemical Resistance	C650	Not Required
Stain Resistance	C1378	Not Required
Freeze/Thaw Resistance	C1378	No sample must show visible signs
Bond Strength	C482	≥ 50 PSI (0.34 MPa)
Surface Hardness	-	7 MOHS
Warpage	C485	Conforms
DCOF (WET)	ANSI A326.3	≥ 0.42
Recycled Material	-	40%



This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Matte Finish
- 8.5mm Thickness
- Pressed Edge
- PEI Rating = 4
- V2 - Slight Shading Variation
- Frost Resistance = Yes



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com