NEOLITH







AVAILABLE IN:


9mm Field Tiles						
SIZE	FINISH		COLORS			
3"x12"	Polished		Bedrock Beige Crystal Gray Mineral Umber			
12"x24"	Matte Polished		Bedrock Beige Crystal Gray Mineral Umber			
24"x24"	Matte Polished		Bedrock Beige Crystal Gray Mineral Umber			
24"x48"	Polished		Bedrock Beige Crystal Gray Mineral Umber			
9mm Mosaics						
SHEET SIZE	ТҮРЕ	FINISH	COLORS			
12"x12"	2"x2" Mosaic	Matte	Bedrock Beige Crystal Gray Mineral Umber			
12"X12"	3" Hex	Matte	Bedrock Beige Crystal Gray Mineral Umber			
9mm Trim Piece						
SHEET SIZE	ТҮРЕ	FINISH	COLORS			
4"x12"	Bullnose	Polished	Bedrock Beige Crystal Gray Mineral Umber			

MADE TO ORDER FIELD TILES AND MOSAICS: Minimum quantity required. Contact your sales representative for more information.

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD	TILES	CUBES		BASKETWEAVE	
	Any 24" field tile		2" 4"		1 ³ / ₈ "x3" 2"x4"
	a smaller size in any length and width	BRICKS		DIAMONDS	
	combination with a 1" minimum.		1"x2" 1"x3" 1 ³ / ₈ "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4"
Diamond	4"			* > >	⁵ / ₈ "×4"
		OCTAGONS		HEXAGONS	
() Hexagon	6"		2"		1 ¹ / ₈ "
Chevron	2"x12" 6"x24"		w/ 0.6" Squares		2"
TRAPEZO	ID W/ DOT	SQUARES		RECTANGLES	
	4"x2 ¹ / ₂ " w/ ⁵ / ₈ " Dot		1"x1" 2"x2" 1 ³ / ₈ "x1 ³ / ₈ " 3"x3"		1"x2" 1"x4"







Bedrock Beige

Mineral Umber



Crystal Gray



2"X2" MOSAIC







Bedrock Beige

Crystal Gray

Mineral Umber

3" HEX MOSAIC







Bedrock Beige

Crystal Gray

Mineral Umber







Features	Test Method	Va	Value	
		Matte	Polished	
Water Absorption	ASTM C373	< 0.5%		
Abrasion Resistance	ASTM C1027	Class 3		
MOHS	Scratch Hardness 1 - 10	7	3	
Breaking Strength	ANSI C648	≥ 425		
Chemical Resistance	ASTM C650	Class A	Class C	
Thermal Shock Resistance	ASTM C484			
Frost Resistance	ASTM C1026	Resistant		
DCOF (WET)	ANSI A 326.3	≥ 0.42		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Matte | Polished Finishes
- 9mm Thickness
- Rectified Edge
- PEI Rating = 3
- V3 Moderate Variation
- Frost Resistance = Yes





www.genrose.com



www.genrose.com