# **SPLENDOR**









12"x24" Field Tile in Amani Bronze 24"x24" Field Tile in Amani Bronze

## **AVAILABLE IN:**

#### 10mm Field Tile

24"x48" Natural | Polished Finish 24"x24" Natural | Polished Finish 12"x24" Natural | Polished Finish 3"x12" Polished Finish

#### Mosaics

9"x11" Sheet 3" Hexagon Natural | Polished Finish

#### **Trim Pieces**

3"x12" Bullnose Natural | Polished Finish

- All sizes are nominal

# MADE TO ORDER FIELD TILES AND MOSAICS:

This represents a small portion of the mosaic patterns we offer.

We can cut any field tile to create a custom mosaic or field tile size as specified.

FIELD TILES		CUBES		BASKETWEAVE	
	Any 24" field tile		2" 4"		1 <sup>3</sup> / <sub>8</sub> "×3" 2"x4"
	a smaller size in any length and width combination with a 1" minimum.	BRICKS		DIAMONDS	
			1"x2" 1"x3" 1 <sup>3</sup> / <sub>8</sub> "x3" 2"x4"		2"
FIELD SHAPES*		CHEVRONS		HERRINGBONE	
Half Hexagon	6.7" Base		2"x12"		1"x2" 2"x4" <sup>5</sup> / <sub>8</sub> "x4"
Diamond	4"	OCTA	CONC	V V V	
Hexagon	6"	OCTAGONS		HEXA	GON2
Chevron	2"x12" 6"x24"		2" w/ 0.6" Squares		1 <sup>1</sup> / <sub>8</sub> " 2"
TRAPEZOID W/ DOT		SQUARES		RECTANGLES	
	4"x2 <sup>1</sup> / <sub>2</sub> " w/ <sup>5</sup> / <sub>8</sub> " Dot		1"x1" 2"x2" 1 <sup>3</sup> / <sub>8</sub> "x1 <sup>3</sup> / <sub>8</sub> " 3"x3"		1"x2" 1"x4"








Amani Bronze

Amani Grey

Marfil





Calacatta

Nero Marquina

## **HEXAGON MOSAIC**



Calacatta



Marfil







Amani Grey

Amani Bronze

Nero Marquina



12"x24" Field Tile in Marfil 24"x24" Field Tile in Marfil





_			
Features	Test Method	Value	
Thickness	ASTM-C499	≤ 0.04 in	
Wedging	ASTM-C502	≥ ± 0.25%	
Warpage	ASTM-C485	≥ ± 0.4%	
Water Absorption	ASTM C373	≤ 0.4%	
Surface Abrasion	ASTM C1027	IV	
Breaking Strength	ASTM C648	≥400 lb/ft²	
Stain Resistance	ASTM C1378	Not Affected	
Chemical Resistance	ASTM 650	Not Affected	
Frost Resistance	ASTM C1026	Resistant	
DCOF (WET)	ANSI-A326.3	≥ 0.42%	
Recycled Content	-	≥40% (Amani Bronze   Nero Marquina)	
Sustainability / Conformance	This product is GREENGUARD® Gold certified and will contribute to USGBC-registered LEED projects. This product complies with ANSI-approved NAHB Green Building Standard ICC 700.		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full, and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

#### **Product Info:**

- Glazed Porcelain Tile
- Natural | Polished Finish
- 10mm Thickness
- Rectified Edge
- PEI Rating = 4
- V3 Moderate Variation
- Frost Resistance = Yes













www.genrose.com