TONBRIDGE







6"x16" Nano Wall Deco in Charcoal 6"x16" Wall Tile in Charcoal



AVAILABLE IN:

10mm Wall Tiles						
SIZE	FINISH		STOCK COLORS	SPECIAL ORDER COLORS		
6"x16"	Satin		White	Charcoal		
10mm Wall Decos						
SIZE	TYPE	FINISH	STOCK COLORS	SPECIAL ORDER COLORS		
6"x16"	Nano Deco	Satin	-	White Charcoal		
6"x16"	Polygon Deco	Satin	-	White Charcoal		
6"x16"	Wave Deco	Satin	White	Charcoal		
10mm Trim Pieces						
SIZE	ТҮРЕ	FINISH	STOCK COLORS	SPECIAL ORDER COLORS		
.5"X12"	Finishing Strip	Satin	White	-		
1"x12"	Pencil*	Satin	White	-		

All Sizes are Nominal.

^{*}Glazed on long side.




6"x16" Wave Wall Deco in White 6"x16" Wall Tile in White





White Charcoal

NANO WALL DECO







Charcoal

POLYGON WALL DECO



White



Charcoal

WAVE WALL DECO



White



Charcoal





Factures	Took Makhad	Value
Features	Test Method	Value
Length / Width	EN ISO 10545 - 2	≤ ± 2.5%
Thickness		± 2.5%
Straightness of Side		± 0.15%
Rectangularity		± 0.4%
Surface Flatness		±0.3%
Water Absorption	EN ISO 10545 - 3	15% to 17%
Weight / M ²	-	10mm Thick
Weight / III		16.67 kg
Modulus of Rupture	EN ISO 10545 - 4	≥ 25N / mm²
Thermal Shock	EN ISO 10545 - 9	Pass
Frost Resistance	EN ISO 10545 - 12	Not Suitable
Chemical Resistance	EN ISO 10545 - 13	Class A - B
Stain Resistance	EN ISO 10545 - 14	Class 3
Fire Rating	-	Class A1 Non Combustible
Recycled Content	-	Up to 20%

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.





Product Info:

- Ceramic Wall Tile
- Satin Finish
- 10mm Thickness
- V1 Uniform Appearance
- Frost Resistance = No



www.genrose.com

Contact your sales representative for more information. All material must be inspected prior to installation. Absolutely no claims will be accepted after installation.



www.genrose.com