

Features	Test Method	Value	
Length / Width	± 0.25%		.25%
Thickness		± 2.5% ± 0.15%	
Straightness of Side	EN ISO 10545 - 2		
Rectangularity	± 0.4%).4%
Surface Flatness		± 0.2%	
Water Absorption	EN ISO 10545 - 3	15% to 17%	
Weight / M ²	-	8mm Thick	10mm Thick
Modulus of Rupture	EN ISO 10545 - 4	14.85 kg 17.78 kg ≥ 25 N / mm ²	
Thermal Shock	EN ISO 10545 - 9	Pass	
Frost Resistance	EN ISO 10545 - 12	Not Suitable	
Chemical Resistance	EN ISO 10545 - 13	Class A - B	
Stain Resistance	EN ISO 10545 - 14	Class 3	
Fire Rating	-	Class A1 Non Combustible	
Recycled Content	-	Up to 20%	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.





Product Info:

- Ceramic Tile
- Gloss Finish
- V1 Uniform Appearance = Arctic White
- V3 Moderate Variation = Seagrass | Mist | Powder Blue
- Frost Resistance = No



www.genrose.com