

Features	Test Method	Value
Nominal Size	ASTM C499	-3% Min 2% Max
Caliber Range	ASTM C499	±.25%
Wedging	ASTM C502	±.25%
Warpage Edge	ASTM C485	±.4%
Warpage Diagonal	ASTM C485	±.4%
Water Absorption	ISO 10545-3	≤ 0.5%
Bending Strength	ISO 10545-4	≥ 45 N/mm ²
Breaking Strength	ISO 10545-4	≥ 2000 N
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	A LA HA
Stain Resistance	ISO 10545-14	5
Thermal Shock Resistant	ASTM C484	Resistant
Visible Abrasion Resistance	ASTM 1027	Dark Colors: 4 Light Colors: 5
DCOF (WET)	ANSI A 137.1- 2012	WET ≥ 0,50
Recycled Material	-	Min 7.5%
	This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.	

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Natural Finish
- 10mm Thickness
- Rectified Edge
- PEI Rating = 5 (Light Colors)
4 (Dark Colors)
- V3 - Moderate Variation (All Other Colors)
- V4 - Substantial Variation (Noce)
- Frost Resistance = Yes

