

Features	Test Method	Value
Thickness	-	9.5mm
Water Absorption	ISO 10545-3	≤ 0.1%
Modulus of Rupture	ISO 10545-4	> 45 N/mm ²
Breaking Strength	ISO 10545-5	≥ 1300N
Scratch Hardness	UNI EN 101	7 Mohs
Abrasion Resistance	ISO 10545-7	5/4
Linear Thermal Expansion	ISO 10545-8	7x10 ⁻⁶ °C ⁻¹
Thermal Shock Resistance	ISO 10545-9	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	LA HA A
Stain Resistance	ISO 10545-14	Class 5
Slip Resistance	DIN 51130	R10 Natural Finish
	DIN 51097	B Natural Finish
DCOF	BS 7976-2	WET ≥ 0.42 Natural Finish
Recycled Material	-	≤ 30%
VOC	-	Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Glazed Porcelain Tile
- Natural Finish
- 9.5mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance = Yes

