

Features	Test Method	Value
<b>Water Absorption</b>	ASTM C373	≤ 0.4%
<b>Warpage Edge</b>	ASTM C485	≥ ± 0.4%
<b>Warpage Diagonal</b>		≥ ± 0.5%
<b>Thickness</b>	ASTM C499	≤ 0.04 in
<b>Wedging</b>	ASTM C502	≥ ± 0.25%
<b>Breaking Strength</b>	ASTM C648	8mm ≥ 300 lb/ft <sup>2</sup> 10mm ≥ 400 lb/ft <sup>2</sup>
<b>Chemical Resistance</b>	ASTM C650	Not Affected
<b>Freeze Resistance</b>	ASTM C1026	Resistant
<b>Stain Resistance</b>	ASTM C1378	Not Affected
<b>D.C.O.F. Acu Test</b>	ANSI A326.3	≥ 0.42%
<b>Recycled Content</b>	-	Matte: ≥ 60% Polished: ≥ 40%
 <p>This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.</p>		

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Glazed Porcelain Tile
- Matte | Polished Finish
- 8mm | 10mm Thickness
- Rectified | Pressed Edge
- PEI Rating = 4
- V3 - Moderate Variation
- Frost Resistance = Yes



[www.genrose.com](http://www.genrose.com)