



Features	Test Method	Value
Length and Width	ISO 10545-2	$\pm 0.5\% \leq \pm 2\text{mm}$
Thickness		$\pm 10\% \leq \pm 0.5\text{mm}$
Straightness of Sides		$\pm 0.3\% \leq \pm 1.5\text{mm}$
Rectangularity		$\pm 0.5\% \leq \pm 2\text{mm}$
Surface Flatness		$\pm 0.5\% \leq \pm 2\text{mm}$
Warpage		$\pm 0.5\% \leq \pm 2\text{mm}$
Water Absorption		ISO 10545-3
Modulus of Rupture / Bending Strength	ISO 10545-4	Ave 15N/mm ²
Breaking Strength		Not Less than 600N
Thermal Shock Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Not Suitable
Chemical Resistance (Domestic)	ISO 10545-13	Min Class B
Stain Resistance	ISO 10545-14	Min Class 3
Recycled Content	-	Up to 20%
VOC Emissions	-	None
 		<p>This product will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700. Low Emissions Material • Zero VOC</p>

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Floor Tile for use in light traffic residential areas.

Product Info:

- Ceramic Tile
- Glossy (Wall) | Matte (Wicker) Finish
- 8mm Thickness
- Pressed Edge
- V1 - Uniform Appearance
- PEI = 2 (Wicker)
- Frost Resistance = No
- Check Decor 24 for Stock



www.genrose.com