


Features	Test Method	Value		
Length And Width	ISO 10545-2	± 0.15%		
Thickness		± 5%		
Warpage Of Edges		± 0.1%		
Wedging		± 0.2%		
Flatness		6mm	9mm	20mm
		± 0.2%	± 0.35%	± 0.35%
Surface Quality	At least 95% of the tiles are free from visible flaws			
Water Absorption	ISO 10545-3	0.08%		
Bending Strength (Avg. Value)	ISO 10545-4	6mm	9mm	20mm
Breaking Strength (Avg. Value)		52 N/mm ²	50 N/mm ²	52 N/mm ²
		1350 N	2200 N	14000 N
Resistance to Deep Abrasion (Avg. Value)	ISO 10545-6	140 mm ³		
Thermal Shock Resistance	SO 10545-9	Resistant		
Frost Resistance	ISO 10545-12	Resistant		
Resistance of Chemical Attack	ISO 10545-13	High Concentration	Low Concentration	Domestic Chemicals
		Soft = UHA - UHB	ULA - ULB	UA
Stain Resistance	ISO 10545-14	6mm	9mm	20mm
		Class 4	Class 3-4	Class 4
Slip Resistance	ANSI 137.1-2012 DCOF	> 0.42		
Recycled Content	-	6mm 9mm - 13.9% Steel, Moka, Plomb; 7.1% Taupe, Sage, Ivory 20mm - 13.47% Ivory; 13.82% Sage; 13.83% Taupe; 15.97% Moka, Plomb; 16% Steel Slabs - 0% Ivory; 7% Others		
VOCs	-	No Emissions		



This product is GREENGUARD® certified and will contribute to USGBC registered LEED projects. It will also contribute to the ANSI approved NAHB Green Building Standard ICC 70.

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Through Body Porcelain Tile
- Matte | Soft | Bush-Hammered | Anti-Slip Finish
- 6mm | 9mm | 20mm Thickness
- Rectified Edge
- V2 - Slight Shading Variation
- Frost Resistance = Yes

