



Features	Test Method	Value
<b>Dimensions and Surface Quality</b>	ISO 10545-2	Complies with the Standard
<b>Water Absorption</b>	ISO 10545-3	≤ 0.5%
<b>Breaking Strength</b>	ISO 10545-4	1,600 – 2,400 N
<b>Bending Strength</b>	ISO 10545-4	35 – 45 N/mm <sup>2</sup>
<b>Thermal Resistance</b>	ISO 10545-9	Resistant
<b>Crazing Resistance</b>	ISO 10545-11	Resistant
<b>Frost Resistance</b>	ISO 10545-12	Resistant
<b>Chemical Resistance</b>	ISO 10545-13	Class A
<b>Stain Resistance</b>	ISO 10545-14	5
<b>DCOF</b>	-	> 0.42
<b>Recycled Material</b>	-	≥31%

This product will contribute to USGBC registered LEED projects.  
 It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.  
 Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be

**Product Info:**

- Porcelain Tile
- Matte Finish
- 9.6mm Thickness
- Pressed Edge
- V1 - Uniform Appearance
- Frost Resistance = Yes


[www.genrose.com](http://www.genrose.com)