

Features	Test Method	Value
Thickness	-	5 mm
Wear Layer	-	0.5mm (20 mil)
Classification	EN ISO 10582	23: Domestic Heavy 32: Commercial General 41: Light Industrial Moderate
Reaction to Fire	EN13501-1 EN ISO 11925-2 EN ISO 9239-1	B _n - S1 Pass Pass
Resistance to Chemicals	EN 423 ASTM F 925	Class 0 Pass
Resistance to Light	EN ISO 105-B02 ASTM F 1515	≥ 6 < 8
Wear Resistance	EN 660-2 ASTM F 510	Wear Group: P
Dimensional Stability	ASTM F 2199 (2014)	Pass
Static Electrical Propensity	EN 1815	Voltage: 0.5kV
Residual Indentation	EN 433 ASTM F 1914	≤0.1 mm <8%
Anti-Slip Property	DIN 51130	R10
VOC Emission	ISO 16000	A+
Phthalates	EN 14372 CPSC-CH-C 1001-09.3	N.D. Pass
Castor Chair Continuous Use	ISO 4918	Pass
Sound Insulation Material Performance (IIC/STC)	ASTM E492-09 (2016)/ ASTM E989-06 (2012)/ASTM E90-09/ ASTM E413-16	66/67

Please Note:

- Lifetime Guarantee: For Residential
- 30 Years Guarantee: For Commercial Uses

Product Info:

- Premium Glue Down/Loose Lay Vinyl Plank Flooring
- 5 mm Thickness
- 20 mil (0.5 mm) Wear Layer
- Beveled Edge
- Check Decor 24 for Stock


www.genrose.com