

Features	Test Method	Value
Water Absorption	ASTM C373-16	≤ 20
Scratch Hardness	C1895-20	2 (All Others) 4 (Black Silver 2)
Breaking Strength	ASTM C648-04	≥ 125 lbs
Chemical Resistance	ASTM C650-04	Class E
Frost Resistance	ASTM C1026-13	No
Stain Resistance	ASTM C1378-04	Class B (All Others) Class A (Black Silver 2)
Recycled Material	-	14%
VOC Emissions	-	Zero VOCs

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Specialty Product Disclaimer:

This is a finely decorative Specialty Product series with metallic or distinctive glazing finishes. These tiles are subject to surface damage when exposed to physical or chemical forces. **Not suitable for use in wet areas.**

Special Cleaning Instructions:

These tiles have a special decorative finish with precious metals or distinctive glazing, and therefore should be cleaned only with a cloth soaked in water and neutral detergent. Do not use acidic or abrasive cleaning products or sponges that may damage the tile surface.



Product Info:

- Ceramic Tile
- Satin Finish
- 9.3mm Thickness
- Rectified Edge
- V1 - Uniform Appearance
- Frost Resistance = No



www.genrose.com