

Features	Test Method	Value
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	1600-2400 N
Modulus of Rupture	ISO 10545-4	35-45 N/mm <sup>2</sup>
Thermal Resistance	ISO 10545-9	Resistant
Crazing Resistance	ISO 10545-11	Resistant
Frost Resistance	ISO 10545-12	Resistant
Chemical Resistance	ISO 10545-13	Household Chemical
		A
Stain Resistance	ISO 10545-14	5
DCOF	ANSI A326.3	0.76
Recycled Material	-	31%



This product will contribute to USGBC registered LEED projects.  
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.  
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Product Info:**

- Color Body Porcelain Tile
- Matte Finish
- 11mm | 12mm Thicknesses
- Rectified Edge
- V1 - Uniform Appearance
- Frost Resistance = Yes



[www.genrose.com](http://www.genrose.com)