

Features	Test Method	Value
Length / Width	EN ISO 10545 - 2	≤ ± 2.5%
Thickness		± 2.5%
Straightness of Side		± 0.15%
Rectangularity		± 0.4%
Surface Flatness		±0.3%
Water Absorption		EN ISO 10545 - 3
Weight / M <sup>2</sup>	-	<b>10mm Thick</b> 16.67 kg
Modulus of Rupture	EN ISO 10545 - 4	≥ 25N / mm <sup>2</sup>
Thermal Shock	EN ISO 10545 - 9	Pass
Frost Resistance	EN ISO 10545 - 12	Not Suitable
Chemical Resistance	EN ISO 10545 - 13	Class A - B
Stain Resistance	EN ISO 10545 - 14	Class 3
Fire Rating	-	Class A1 Non Combustible
Recycled Content	-	Up to 20%

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.



**Product Info:**

- Ceramic Wall Tile
- Satin Finish
- 10mm Thickness
- V1 - Uniform Appearance
- Frost Resistance = No



[www.genrose.com](http://www.genrose.com)