

Features	Test Method	Value
<b>Water Absorption</b>	ASTM C373-16	≤ 20
<b>Scratch Hardness</b>	C1895-20	4
<b>Breaking Strength</b>	ASTM C648-04	≥ 125 lbs
<b>Chemical Resistance</b>	ASTM C650-04	Class E
<b>Frost Resistance</b>	ASTM C1026-13	No
<b>Stain Resistance</b>	ASTM C1378-04	Class A
<b>Recycled Material</b>	-	14%
<b>VOC Emissions</b>	-	Zero VOCs

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

**Specialty Product Disclaimer:**

This is a finely decorative Specialty Product series with metallic or distinctive glazing finishes. These tiles are subject to surface damage when exposed to physical or chemical forces. **Not suitable for use in wet areas.**

**Special Cleaning Instructions:**

These tiles have a special decorative finish with precious metals or distinctive glazing, and therefore should be cleaned only with a cloth soaked in water and neutral detergent. Do not use acidic or abrasive cleaning products or sponges that may damage the tile surface.



**Product Info:**

- Ceramic Tile
- Satin Finish
- 9.3mm Thickness
- Rectified Edge
- V1 - Uniform Appearance
- Frost Resistance = No



[www.genrose.com](http://www.genrose.com)