

| Features | Test Method | Value |
|--------------------------|-----------------|--|
| Length and Width | ISO 10545-2 | ±0.6% (±2.00 mm) |
| Thickness | | ±5% (±0.5 mm) |
| Warpages of Edges | | ±0.5% (±1.5 mm) |
| Wedging | | ±0.5% (±2.00 mm) |
| Flatness | | ±0.5% (±2.00 mm) |
| Water Absorption | ISO 10545-3 | ≤ 0.5% |
| Bending Strength | ISO 10545-4 | R ≥ 35 N/mm ² S > 1300 N |
| Linear Thermal Expansion | ISO 10545-8 | ≈7x10 ⁻⁶ C ⁻¹ |
| Thermal Shock Resistance | ISO 10545-9 | Resistant |
| Frost Resistance | ISO 10545-12 | Resistant |
| Chemical Resistance | ISO 10545-13 | Resistant |
| Stain Resistance | ISO 10545-14 | ≥ Class 3 |
| Color Resistant to Light | DIN 51094 | No Alteration |
| DCOF (Wet) | ANSI 137.1-2012 | 0.55 |
| Recycled Material | - | 10% |





This product will contribute to USGBC registered LEED projects.
It will also contribute to the ANSI approved NAHB Green Building Standard ICC 700.
Low Emissions Material • Zero VOC

According to ANSI and MIA standards, depending on the type and size of tile, it is recommended to have at least a 1/8" wide grout joint for floor tiles in order to be able to fill the grout joint full and never less than 1/16" wide. Please refer to TCNA guidelines for more on grout recommendations.

Product Info:

- Color Body Porcelain Tile
- Natural Finish
- 9.5mm Thickness
- Rectified Edge
- V3 - Moderate Variation
- Frost Resistance = Yes



www.genrose.com